



SCOUT

## EMERGENCY LIGHTING



Specifically designed to depart from the norm and please architects and consultants, while maintaining the contractors needs as a priority during installation in prestigious areas.

Purpose designed for interior use, the **Scout** luminaire houses a unique swivel and rotate system, which allows independent positioning of the projectors, giving the installer more flexibility on installation.

Unlike other twin projector luminaires, the **Scout** not only includes a unique rotate reflector system, but also an aesthetically pleasing compact enclosure which will blend into almost any decor, where open area lighting must be provided to direct persons escaping onto the defined escape route.

Designed and tested to all relevant standards and EU Directives, the **Scout** is an exciting new class of Emergency Lighting product, offering unique features and a whole new opening in an ever-changing marketplace.

Surface mounting or semi-recessed, the **Scout** is the only option for discreet and stylish Emergency Lighting installations.

Easy to install and maintain and comes with a full 3 year warranty.

3

3 YEAR  
WARRANTY

# VENTILUX





**VENTILUX**  
manufactures and supplies an extensive range of emergency lighting, standby power and fire detection equipment.

The company pays close attention to the quality, specification and construction of its products and is able to offer a comprehensive system design capability to allow the effectiveness of each installation to be maximised.

With Ventilux installations operating worldwide, the company works in close association with distributors and a number of specialist emergency lighting conversion centres throughout its market.

## DESIGN FEATURES/BENEFITS

- Incorporates a new swivel and rotate reflector system, which allows the user to highlight a wider area.
- Designed to be both ceiling & wall mounted.
- Purpose designed for prestigious interiors to blend and compliment the existing aesthetic.
- Ease of installation and maintenance.
- Slim-line enclosure can be semi-recessed to the lid level. Designed to comply with all current standards along with the appropriate requirements of EU Directives.
- Designed in aluminium and chrome to blend into design-conscious environments. Alternative finishes available on request.
- Specifically designed reflector to maximise lumen output for 10/20 Watt Tungsten Halogen lamps.
- Stylish alternative to existing product form.
- Ventilux full 3 year warranty as standard.

## SAMPLE SPECIFICATION

- Twin spot, non-maintained emergency lighting luminaire.
- 2 x 10 Watt/2 x 20 Watt Tungsten Halogen twin projector luminaire for 3 Hour/1 Hour duration.
- Constant voltage charger to provide full recharge of batteries within 24 Hours.
- Low voltage cut-off circuit for deep discharge protection of batteries.
- LED indication of correct charger functioning and lamp filaments intact.
- Maintenance free sealed lead acid battery.
- Steel and aluminium enclosure of maximum dimensions 342mm x 214mm x 132mm.
- 20mm Dia. Conduit entries in side and back surfaces.
- Complies with all relevant requirements of EN60598.2.22:1990 (BS4533 Pt 102.22:1990) and EN55015
- 3 year product warranty.

**As Ventilux Compact Twinspot (CTL --)**

Order Codes	SC20/NM3	SC10/NM3	SC55/NM1
Mode of Operation	Non-maintained	Non-maintained	Non-maintained
Tungsten Halogen Projectors	2 x 20 Watt	2 x 20 Watt	2 x 55 Watt
Emergency Duration	3 Hour	3 Hours	1 Hour
Degree of Protection	Interior/IP42	Interior/IP42	Interior/IP42
Housing Construction	Steel finish Housing with Aluminium lid		
Input Voltage (Other voltages on request)	230V ±10% 50/60 Hz	230V ±10% 50/60 Hz	230V ±10% 50/60 Hz
Battery Charger	Automatic, Current Limited, Constant Voltage		
Charging/Lamp Filament Monitor	High Intensity Red LED	High Intensity Red LED	High Intensity Red LED
Recharge Period	24 Hours for full Recharge		
Overall Dimensions (mm)	350W x 220H x 160D	350W x 220H x 160D	350W x 220H x 160D
Battery	12V 14 Ah	12V 7 Ah	12V 14 Ah
Power Consumption	40 VA	40 VA	40 VA
Cable Entries	20mm Entries on side and rear surface		
Weight	7.8kg	5.4kg	7.8kg
Environment	-10°C to +30°C Temperature range; Up to 80% Relative Humidity		
Warranty	3 Years	3 Years	3 Years



**VENTILUX**  
LIMITED

UNIT 2  
ASHGROVE INDUSTRIAL ESTATE  
KILL AVENUE  
DUN LAOGHAIRE  
COUNTY DUBLIN  
IRELAND

TELEPHONE  
(INT) + 353 (0)1 214 8800  
FACSIMILE  
(INT) + 353 (0)1 280 5729

E-MAIL  
user@ventilux.ie

SYSTEMS HOUSE  
WILDMERE ROAD  
WILDMERE INDUSTRIAL ESTATE  
BANBURY, OXON OX16 7JU  
UNITED KINGDOM

TELEPHONE  
(INT) + 44 (0) 1295 279995  
FACSIMILE  
(INT) + 44 (0) 1295 276799

E-MAIL  
user@ventilux.prestel.co.uk

www.  
ventilux.ie

